



LIST "MARQUIS STUDENT" K.D. TRIPLE TIER LOCKER (18" OR 24" WIDE) (PRODUCT No. LMS _ _ _ _ _ -3_)

ELEVATION ' ' /



SIDE VIEW



FRONT VIEW

LOCKER DETAILS:

DOOR & FRAME COLOR =
 BODY COMPONENT COLOR = 729 PARCHMENT
 TOP =
 HANDLE = SINGLE POINT (S.S. RECESSED DRAWN)
 DOOR VENTILATION = PLAIN
 OPTIONAL SECURITY-PLUS VENTS SHOWN
 SIDE VENTILATION = SOLID
 BASE =
 LOCKS =
 HINGE = CONTINUOUS PIANO HINGE

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4" FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

GAUGES

DOOR = 14 GA., C.R.S.
 STIFFENER = 18 GA., C.R.S.
 FRAME = 16 GA., C.R.S.
 TOP = 24 GA., C.R.S.
 BASE = 24 GA., C.R.S.
 SHELVES = 24 GA., C.R.S.
 SIDES = 24 GA., C.R.S.
 BACKS = 24 GA., C.R.S.

LATCHING: (WARDROBE) SINGLE POINT RECESSED LOCKING DEVICE PREPARED FOR BOTH PADLOCK AND BUILT-IN LOCKS.

SUPERIOR

THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY LIST INDUSTRIES RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES.

TOLERANCES UNLESS SPECIFIED:
 FRACTIONS: ±1/32 DECIMALS: ±0.010 DEGREES: ±1'

Customer: CUSTOMER
 Customer Order Number: PO#
 Description: JOB NAME
 JOB LOCATION

Drawn By: DRAFTER	Checked By:	Date: DATE	Scale: NONE
Acad Number: PAGE NUMBER		Sheet # Of #	Revision:
Drawing Number:		FOLDER NUMBER	