LIST "P.E. SERIES" SIX TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. LWA _ _ _ -6)

ELEVATION ' '



SIDE VIEW



FRONT VIEW

LOCKER DETAILS:

EXTERIOR COLOR =
INTERIOR COLOR = SAME AS EXTERIOR
TOP =
HANDLE = SINGLE POINT, SPRING LATCH
DOOR VENTILATION = 7/16" x 15/16" DIAMOND
SIDE VENTILATION = 1/2" 13 GA. FLT/EXP/MTL
BASE =
LOCKS =
HINGE = 3/16" DIAMETER CONTINUOUS HINGE ROD WITH CONCEALED FASTENER.

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4" FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

GAUGES

DOOR =	14 GA., C.R.S
FRAME =	16 GA., C.R.S
TOP =	16 GA., C.R.S.
BOTTOM =	16 GA., GALVANNEAL
HAT SHELVES =	16 GA., GALVANNEAL
INT/MED SHELVES =	16 GA., GALVANNEAL
SIDES =	1/2" 13 GA. FLT/EXP/MTL, H.P.D
BACKS =	18 GA., C.R.S.

LATCHING: (BOX DOOR, TOP HINGE) SINGLE POINT HEAVY DUTY SPRING LATCH.

HINGES: (BOX DOOR, TOP HINGE) 3/16" DIAMETER CONTINUOUS HINGE ROD WITH CONCEALED FASTENER.

SUPERIOR

THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY LIST INDUSTRIES RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES.

TOLERANCES UNLESS SPECIFIED:
FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°

Customer: CUSTOMER
Customer Order Number: PO#
Description: JOB NAME
JOB LOCATION

Drawn By:	Checked By:	Date:	Scale:
DRAFTER		DATE	NONE

Acad Number: PAGE NUMBER | Sheet # Of # | Revision:

Drawing Number: FOLDER NUMBER